

acm **acmaudio**
PS3-1000



acm **acmaudio**
PS3-1000



PS IMPACT consists of two satellites and a subwoofer equipped with a power amp and all the electronics required to drive the bass bin and satellite. The electronic circuitry protects it from overloads and makes this system very easy to operate.

An ACM AUDIO active system is so much more than merely a pair of active cabinets on tripods; it is an end-to-end sound-reinforcement solution consisting of subwoofer, satellites and meticulously matched circuitry.

Specifications

Technical Data	PS3-1000 SATELLITE
Power-handling nominal	150 W RMS (80 Hz/125Hz, low cut)
Frequency response	+/- 3dB 80 Hz/125 Hz-20 kHz
Axial sensitivity 1W@1m	95 dB
Maximum SPL @1m	120dB
Nominal impedance	8 ohms
Midrange woofer	1x 8"
Tweeter	Driver 1"
Directivity	90° x 60°
Connections	1x Speakon® NL 4

Physical Properties	
Height	16.5in/420mm
Width	10.4in/265mm
Depth	9.4in/240mm
Weight	21lb/9.5kg

Technical Data	PS3-1000 SUBWOOFER
Frequency response +/- 3dB	40 Hz-80-200Hz
Axial sensitivity 1W@1m	99 dB
Maximum SPL @1m	130dB
Subwoofer amplifie	1x 600 W RMS / Class AB
Sat & Mid/High Unit amp	2x 200 W RMS / Class AB
Connections	2x XLR In, 2x jack MIC IN 2xXLR OUT, 2x Speakon® Satellite out
Subwoofer	1x15"
Operating Temperature Range	-10° C to 55° C (14° F to 13° F)

Physical Properties	
Height	21.4in/545mm
Width	17.7in/450mm
Depth	25in/635mm
Weight	106.7lb/48.5kg