



acm **acmaudio**  
**SRL10**

acm **acmaudio**  
**SRL10**



The SRL Active and Passive Series from 10", 12" to 15" offer truly professional sound to musicians and DJs working small to medium venues live performance. The full range 2-way systems function either as mains or as monitors by 45 or 60 degree and can be mounted on pole stands. The portable, full range loudspeakers are optimized for use with the ACM subwoofer, which also serves as a pole mount base. Additionally, any ACM subwoofer will complement the SRL Series. The full range models include threaded mounting points for installation applications.

**Technical Specification:**

Freq. Range (-10dB):	65Hz--20KHz
Freq. Response (-3dB):	75Hz--20KHz
Rec.Hipass Frequency:	50Hz
Axial Sensitivity:	96dB (1W/1m)
Max Calculated SPL:	126dB
Horizontal Coverage:	80°
Vertical Coverage:	60°
Rated System Power:	250W Continuous 1000W Peak
LF Transducer:	10"/65mm
HF Transducer:	1"/45mm
Crossover Frequency:	2.1kHz
Nominal Impedance:	8 ohms
Connector:	2 x NL4 Speakon
Dim(H x W x D)	536mm x 315mm x 315mm
Net Weight:	17Kg
Shipping Weight:	19Kg

