



SRP 115SE is a compact, active subwoofer system. Through the use of proprietary amplifier technology, precision manufactured woofer technology and the innovative implementation of a high efficiency chamber design, SRP 115SE deliver tight, fast, controlled bass response.

Optional balanced and unbalanced signal input, Adjustable 80 to 200 Hz low pass filter. OFF/80Hz/125Hz high pass filter, phase reverted switch available, Built-in power limit protection circuit.

Technical Specification:

<i>Freq. Range (-10dB):</i>	<i>45Hz~220Hz</i>
<i>Freq. Response (-3dB):</i>	<i>50Hz~200Hz</i>
<i>Max Calculated SPL:</i>	<i>130dB</i>
<i>Amplifier Power:</i>	<i>600W</i>
<i>LF Transducer:</i>	<i>15"/100mm</i>
<i>Crossover Frequency:</i>	<i>80Hz~200Hz Adjustable</i>
<i>Connector:</i>	<i>Line XLR/RCA</i>
<i>Output Connector:</i>	<i>Pre output XLR</i>
<i>Input Impedance:</i>	<i>Balance 20k/nobalance 47k</i>
<i>AC Input:</i>	<i>AC115V/230V 50Hz/60Hz</i>
<i>Dim (W×H×D)</i>	<i>450mm×560mm×720mm</i>
<i>Net Weight:</i>	<i>49Kg</i>
<i>Shipping Weight:</i>	<i>52Kg</i>

